Countertop Payment Terminals



- Dial & IP Dual Comm - EMV Chip Reader - PCI internal PIN Pad - Contactless Reader Standard with all the following features: for Fay, Google Wallet, Samsung Pay

*Optional built in Wi-Fi for **Tri-Comm** compatibility!

GOGreen

Send Electronic Receipts!

EMV Certified



The Z11 and Z8 countertop payment terminals provide an easy to use EMV payment experience for every business owner. With "On screen Help", easy access to frequently used options in the "Favorites" Menu, and a simple "Call Me" button to request a support representative callback, merchants love the ease of use and ISOs love the easy programming of Dejavoo.

The Z11 has a bright color touchscreen for signature right on the display for signature capture and easy upload to the DeNovo business portal. Customize your Dejavoo payment device with a logo on the display. Upload multiple images programmed to scroll while the terminalis in idle mode!

GOGreen with electronic receipt options, send receipts to consumers via email or sms text message!

















Dejavoo Sofware Features Available on All Devices:

- ✓ Restaurant EMV Tip Adjust Post Authorization
- ✓ Built in Loyalty Program no loyalty cards or host communication needed!
- Connects with DeNovo business portal for transaction upload, signature capture, loyalty back up, batch notification, Call Me, Messaging & more.
- ✓ Optional WiFi models for Tri Comm (IP, Dial & WiFi) with Quick and Easy WiFi set up. Terminal finds available networks!
- ✓ **GO**Green with electronic receipt options, send receipts to consumers via email or sms text message!
- ✓ Integrates with Dejavoo SPIn easily and effortlessly
- ✓ Logo can be uploaded to display on screen
- ✓ Free access to facilitate and manage your own merchant download profiles via the Dejavoo STEAM file build system.













ZLine Countertop Series			Z11 Touch Screen	Z8 Dual Comm	
Processor			32 bits 400 MHz Secure Microprocessor		
Memory	Flash / DDR RAM		128 MB/64MB		
	Micro SD Socket		Optional		
Display			3.5" Color TFT-LCD ~ 320X480 Pixels	2.4" Color LCD ~ 320X4240 Pixels	
Touch Screen			✓	X	
Card Readers	Magnetic Strip (Standard)		ISO 7810, 7811 & 7813 Triple Track Bi-Directional		
	Contact Card	User Card	ISO 7816 ID-1 1.8V/3V/5V T=0, T=1		
		SAM Card (up to 4)	2	2	
	Contactless (Standard)		ISO 14443 Type A, B, ISO 18092 NFC and Milfare® and SONY® Felica ~ Working frequency 13.56MHz		
Communications (Dual Comm is Standard)			Ethernet, Dial-up Modem, 2x RS232, 2xUSB WiFi (Optional)		
Indicator	LED – 4 LEDs		X	✓	
Keypad			15 Standard Keys	15 Standard Keys	
Function Keys			X	6	
Weight			7.5"X 3"X 3"		
			.77 lbs	.77 lbs	
Environment	Operating Temperature		32°F to 150°F		
	Storage Temperature		-4°F to 158°F		
Graphical Printer			2.25" X 80', 4"/second	2.25" X 80', 4"/second	
Certifications Security		Payment	PCI PTS, EMV L1 L2, TQM, PBOC L1 L2 Visa PayWave, MasterCard PayPass, American Express, & JCB J/ Speedy		
	Safety, EMC		CE, FCC, BSMI, RoHS		
Software			SDK, KMS, TMS, Simulator, CTOS library, ISO 8583 library, Crypto library		
Crypto			TRNG, DES, T'DES, AES, RSA, MK/SK, DUKPT, T'DES DUKPT		



www.firstpay.ca

9131 Keele St. Unit A4, Vaughan ON, L4K 0G7

Phone: 289-818-2994 Email: info@firstpay.ca